DETAILS OF PRODUCT OFFERING

Summary of Vehicle Offering



City of Marquette Oshkosh P-Series Chassis

Selection	Item Description
P Series 4 X 4	4 X 4 P Series Chassis 158" Wheel Base CA 91" and AE 40"
	TATT COILCE CHARGIN FOR WHOM BASE CATCH WITH ALL TO
FRAME AND FRAME EQUIPMENT	
STANDARD	12-3/8 x 3-7/8 x 3/8 Single Channel rail, 120,000 lb. alloy steel; 2,818,000 RBM
STANDARD	24 " Integral front frame extension
STANDARD	Mud flaps for front axle
OPTION	170" 4 X 4 Wheel base
STANDARD	40" 4 X 4 AE
STANDARD	Low Mount - T/Case mounted below the top of the frame rail
OPTION	Hitch Steps, Cheekplate - Shiploose
ENGINE, CHASSIS	
OPTION	Engine, 2013 Cummins ISX 450 HP
STANDARD	Engine Warranty, Two Years (Cummins)
STANDARD	Ether start kit (Cummins)
STANDARD	Coolant spin on filter (Cummins)
STANDARD	Premium hoses, radiator and heater
STANDARD	Black Exhaust Superstack with rain cap
FUEL	
FUEL STANDARD	United firellimeter conceptor
STANDARD	Heated fuel/water separator
STANDARD	Brass plugs in the bottom of fuel tank
OPTION	75 Gallon single tank, left side
TRANSMISSION	
STANDARD	Transmission temp warning light
STANDARD	Transynd Synthetic Transmission Lubricant
OPTION	Transmission Upgrade, 4000 RDS GEN IV 5-speed ipo 4000 RDS 4-speed
TRANSFER CASE	
OPTION	Dorr-Miller 2-SPEED Auto Locking / Unlocking
NOTES	DEALER/CUSTOMER TO VERIFY WITH OSHKOSH GEAR RATIO FOR SPEED/PERFORMANCE
==	
AXLES	
STANDARD	Front Axle 25K (P Series)
OPTION	Rear Axle 26K All Wheel Steer
OPTION	Driver Controlled Rear Axle Differential
NOTE:	6.14 Front Axle Ratio / 6.17 Rear Axle Ratio (AWS)
BRAKES & AIR SYSTEM	
STANDARD	Dual system, anti-lock, air operated mechanical brakes
STANDARD	Air Compressor 18.7 CFM Turbo Charged
STANDARD	Air Dryer - AD-IS
STANDARD	Quick Drain Cables for Air Tanks
FRONT TIRES	
STANDARD	395/85R20 MVT Goodyear
NOTES	Dealers responsible to contact Oshkosh to verify tires and axle ratios will synchronize
REAR TIRES	
STANDARD	395/85R20 MVT Goodyear
Spare Wheel and Tire	
SPARE	395/85R20 MVT Goodyear (1 Front / 1 Rear)
CAB & CAB EQUIPMENT	
STANDARD	Rubber Mounted Cab
STANDARD	Stainless Steel Grill
STANDARD	Heated Mirrors
STANDARD	Windshield Washer Reservoir 6 qt
STANDARD	Stationary Rear Window
STANDARD	Doors and Ignition Keyed Differently
STANDARD	Driver and Passenger Seat, Bostrom Air-400RX Black, High Back, Fixed Lumbar Support
STANDARD	Heater, Capacity 50,000 BTU, High Output
STANDARD	Douglas Tilt/Telescopic Steering Column
OPTION	Radio AM/FM with Weather Band, CD Player, XM Ready
OPTION	High Idle Switch/Cruise Control (30 MPH and above)
STANDARD	Visor Non- Padded (tinted)
STANDARD	Visit Noti - Added (Inited) Lubrication Data Plate
STANDARD	One (1) Electric Horn

ELECTRICAL SYSTEM & FEATURES STANDARD

Alternator - 170 amp
Engine Compartment Light
Battery Box with Three (3) Batteries
Aux Lighting Switch Kit
Master Electrical Kit STANDARD STANDARD OPTION OPTION

DETAILS OF PRODUCT OFFERING

Summary of Vehicle Offering



City of Marquette Oshkosh P-Series Chassis

Selection	Item Description
EXTERIOR LIGHTING	
	Beacons & Strobes, Cab
OPTION	Strobe, Amber LED, Ship Loose (Dealer/Customer Install)
Work and Driving, Cab	
OPTION	Switch Kit For Work lights (no lights)
PAINT & RUSTPROOFING	
STANDARD	Dupont 7744D Lime Green
MANUALS	
STANDARD	Parts Manuals via Internet Access
STANDARD	One (1) paper copy of Operator's, Parts & Service Manuals
SHIP LOOSE ITEMS	
STANDARD	Tow Hooks, Two (2) mounted at rear and two (2) shipped loose
WARRANTY	
STANDARD	One Year Standard
ADDITIONAL ITEMS	
On-Site Training	Supplied and Provided by Industrial Marketing
Freight	FOB City of Marquette, MI (Chassis Only)